

# ALPHA

## MEDIUM ALPHA ROUND


### SPOTLIGHT



LAST UPDATE: 19-08-2026



ALPHA is an entirely new family of outdoor spotlights/floodlights engineered from scratch. The primary shapes and overall small dimensions make it possible to install ALPHA in most professional and residential lighting applications. High-quality polycarbonate optics provide accurate beam control and offer a wide selection of light distributions. ALPHA can be customized with accessories such as honeycombs, shields and various mounting solutions for poles and surfaces. The minimized amount of needed tools and usage of quick connectors simplifies the installation.



### Technical Data



|                       |                    |
|-----------------------|--------------------|
| Ordering Code :       | 5925-D-5-536-XX    |
| Lamp :                | LED                |
| Beam :                | 42°                |
| CCT :                 | 4000 K             |
| CRI :                 | CRI >80            |
| SDCM :                | SDCM = 3           |
| Lamp Lumen :          | 3330 lm            |
| Luminaire Lumen :     | 2020 lm            |
| Lamp Wattage :        | 26 W               |
| Luminaire Wattage :   | 27 W               |
| Efficacy :            | 74 lm/W            |
| Ambient Temperature : | 50°C               |
| Lumen Maintenance     | L80B10 >108,000 h  |
| Controller :          | DALI               |
| Input Voltage :       | 220-240Vac 50/60Hz |
| Net Weight :          | 3.10 kg.           |

#### Ordering code guide

XXXX-X-X-XXX-XX  
A B C D E

A Product Code  
B Reflector  
C Electrical Component  
D Lamp  
E Color



Icon definition

\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1  
Fax : +66(0)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# ALPHA

## MEDIUM ALPHA ROUND

### SPOTLIGHT





LAST UPDATE: 19-08-2026

#### Specification

|                         |                                                                                                                                                                                                                                                     |  |          |  |             |  |              |  |                    |  |          |  |           |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------|--|-------------|--|--------------|--|--------------------|--|----------|--|-----------|
| IEC Standard            | IEC 60598-1 General Requirement<br>IEC 60598-2-1 Fixed Luminaires                                                                                                                                                                                   |  |          |  |             |  |              |  |                    |  |          |  |           |
| Protection              | IP66 Class I                                                                                                                                                                                                                                        |  |          |  |             |  |              |  |                    |  |          |  |           |
| IK Rating               | Protection against mechanical impact IK10 on body and IK08 on optical part.                                                                                                                                                                         |  |          |  |             |  |              |  |                    |  |          |  |           |
| Luminaires Body Housing | High-pressure die cast aluminum alloy body and components.                                                                                                                                                                                          |  |          |  |             |  |              |  |                    |  |          |  |           |
| Coating Process         | Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.                   |  |          |  |             |  |              |  |                    |  |          |  |           |
| Diffuser                | Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.                                                                                                                                                        |  |          |  |             |  |              |  |                    |  |          |  |           |
| Lens                    | Molded PC lens from renowned manufacturers in various light distribution patterns.                                                                                                                                                                  |  |          |  |             |  |              |  |                    |  |          |  |           |
| Adjustable Optic        | Adjustable aiming unit through graduated scale.                                                                                                                                                                                                     |  |          |  |             |  |              |  |                    |  |          |  |           |
| Gasket                  | Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.                                                                                                                                         |  |          |  |             |  |              |  |                    |  |          |  |           |
| External Screws         | External screws are in stainless steel with protection grease.                                                                                                                                                                                      |  |          |  |             |  |              |  |                    |  |          |  |           |
| Cable Entry             | Cable entry protected by M20 cable gland. To be used with H05RN-F/ H07RN-F cable with 7-13mm. diameter.                                                                                                                                             |  |          |  |             |  |              |  |                    |  |          |  |           |
| Led                     | High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.                                                                                                          |  |          |  |             |  |              |  |                    |  |          |  |           |
| Driver                  | High quality DALI Driver in constant current. Conform to applicable safety standards and electromagnetic compatibility.                                                                                                                             |  |          |  |             |  |              |  |                    |  |          |  |           |
| Internal Wire           | Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.                                                                                                                                   |  |          |  |             |  |              |  |                    |  |          |  |           |
| Terminal Block          | Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.<br>Class1 luminaire provided with the earth connection.                                                                                                      |  |          |  |             |  |              |  |                    |  |          |  |           |
| Caution                 | Installation work has to be carried on according to the enclosed installation manual.                                                                                                                                                               |  |          |  |             |  |              |  |                    |  |          |  |           |
| Color                   | <table><tr><td></td><td>Black O1</td></tr><tr><td></td><td>Graphite O2</td></tr><tr><td></td><td>Dark Grey O3</td></tr><tr><td></td><td>Aluminum Silver O4</td></tr><tr><td></td><td>White O6</td></tr><tr><td></td><td>Corten O8</td></tr></table> |  | Black O1 |  | Graphite O2 |  | Dark Grey O3 |  | Aluminum Silver O4 |  | White O6 |  | Corten O8 |
|                         | Black O1                                                                                                                                                                                                                                            |  |          |  |             |  |              |  |                    |  |          |  |           |
|                         | Graphite O2                                                                                                                                                                                                                                         |  |          |  |             |  |              |  |                    |  |          |  |           |
|                         | Dark Grey O3                                                                                                                                                                                                                                        |  |          |  |             |  |              |  |                    |  |          |  |           |
|                         | Aluminum Silver O4                                                                                                                                                                                                                                  |  |          |  |             |  |              |  |                    |  |          |  |           |
|                         | White O6                                                                                                                                                                                                                                            |  |          |  |             |  |              |  |                    |  |          |  |           |
|                         | Corten O8                                                                                                                                                                                                                                           |  |          |  |             |  |              |  |                    |  |          |  |           |

#### Light Distribution



\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1  
Fax : +66(0)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# ALPHA


## MEDIUM ALPHA ROUND

### SPOTLIGHT



LAST UPDATE: 19-08-2026

#### Bug Report



| Lum. Classification System (LCS) |           |          |       |       |
|----------------------------------|-----------|----------|-------|-------|
| LCS                              | Zone      | %Lumens  | %Lamp | %Lum  |
| FL                               | [0-30]    | 699.1    | 21.0  | 34.6  |
| FM                               | [30-60]   | 268.1    | 8.0   | 13.3  |
| FH                               | [60-80]   | 38.8     | 1.2   | 1.9   |
| FVH                              | [80-90]   | 1.7      | 0.1   | 0.1   |
| BL                               | [0-30]    | 699.1    | 21.0  | 34.6  |
| BM                               | [30-60]   | 268.1    | 8.0   | 13.3  |
| BH                               | [60-80]   | 38.8     | 1.2   | 1.9   |
| BVH                              | [80-90]   | 1.7      | 0.1   | 0.1   |
| UL                               | [90-100]  | < 0.05   | 0.0   | 0.0   |
| UH                               | [100-180] | 5.0      | 0.1   | 0.2   |
| Total                            |           | 2020.4   | 60.7  | 100.0 |
| BUG Rating                       |           | B2-U1-G0 |       |       |

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

# ALPHA

## MEDIUM ALPHA ROUND

### SPOTLIGHT




LAST UPDATE: 19-08-2026


#### Accessories



Ordering Code:  
AUN-CON-0011-00  
IP68 connection device,  
cable diameter 7.1-13mm,  
1-10V or DALI



Ordering Code:  
AUN-GSH-0012-00  
Honeycomb louver, LED,  
pre-assembly from factory




Ordering Code:  
AUN-SOF-0026-00  
Softening filter, LED,  
pre-assembly from factory




Ordering Code:  
AUN-CON-0014-00  
IP68 connection device,  
cable diameter 8-12.5mm,  
1-10V or DALI




Ordering Code:  
AUN-CLP-0004-XX  
Pole clamp, pole diameter  
102-105mm




Ordering Code:  
AUN-GHS-0028-XX  
Glare shield cap




Ordering Code:  
AUN-CLP-0006-XX  
Pole clamp, pole diameter  
60-76mm



Ordering Code:  
AUN-MOT-0013-XX  
Pole mounting arm, for 1-3  
projector



Ordering Code:  
AUN-CLP-0008-XX  
Pole clamp, pole diameter  
102-105mm, for wall or  
pole mounting arm



Ordering Code:  
AUN-CLP-0009-XX  
Pole clamp, pole diameter  
60-76mm, for wall or pole  
mounting arm



Ordering Code:  
AUN-ESP-0001-00  
Earth spike, GFR polymer



Ordering Code:  
AUN-TRS-0001-00  
Tree strap, small mounting  
base

# ALPHA

## MEDIUM ALPHA ROUND

### SPOTLIGHT



LAST UPDATE: 19-08-2026



Ordering Code:

ALUMINUM-POLE-FOR-ALPHA-SPOTLIGHT

Please contact Sales

Representative



Ordering Code:

STEEL-POLE-FOR-ALPHA-SPOTLIGHT

Please contact Sales


Representative



Ordering Code:

AUN-CAB-0012-00

Cable H05RR-F 5x1, L= 2000mm, with UniBlock anti-humidity kit, pre-assembly from factory



Ordering Code:

AUN-BRK-0014-XX

Mounting bracket, pre-assembly from factory

\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th