# ALPHA

## MINI ALPHA SQUARE ARM

### SPOTLIGHT

LAST UPDATE: 13-02-2026



ALPHA is an entirely new family of outdoor spotlights/floodlights engineered from scratch. The primary shapes and overall small dimensions make it possible to install ALPHA in most professional and residential lighting applications. High-quality polycarbonate optics provide accurate beam control and offer a wide selection of light distributions. ALPHA can be customized with accessories such as honeycombs, shields and various mounting solutions for poles and surfaces. The minimized amount of needed tools and usage of quick connectors simplifies the installation.




## Technical Data

IP66 IK 08 06

| | |
|---|---|
| Ordering Code : | 5946-A-3-677-XX |
| Lamp : | LED |
| Beam : | 15° |
| CCT : | 2700 K |
| CRI : | CRI >80 |
| SDCM : | SDCM = 3 |
| Lamp Lumen : | 1040 lm |
| Luminaire Lumen : | 880 lm |
| Lamp Wattage : | 8.4 W |
| Luminaire Wattage : | 10 W |
| Efficacy : | 88 lm/W |
| Ambient Temperature : | 50°C |
| Lumen Maintenance | L80B10 >108,000 h |
| Controller : | On-Off |
| Input Voltage : | 220-240Vac 50/60Hz |
| Net Weight : | 2.00 kg. |

### Ordering code guide

XXXX-X-X-XXX-XX

A Product Code
B Reflector
C Electrical Component
D Lamp
E Color

IK BODY OPTIC Icon definition

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

# ALPHA

## MINI ALPHA SQUARE ARM

### SPOTLIGHT

LAST UPDATE: 13-02-2026

## Specification

| | |
|---|---|
| IEC Standard | IEC 60598-1 General Requirement |
| | IEC 60598-2-1 Fixed Luminaires |
| Protection | IP66 Class I |
| IK Rating | Protection against mechanical impact IK08 on body and IK06 optical part. |
| Luminaires Body Housing | High-pressure die cast aluminum alloy body and components. |
| | Extruded aluminum S6063 alloy body with low copper content. |
| Coating Process | Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C. |
| Diffuser | Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. |
| Lens | Molded PC lens from renowned manufacturers in various light distribution patterns. |
| Adjustable Optic | Adjustable aiming unit through graduated scale. |
| Gasket | Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C. |
| External Screws | External screws are in stainless steel with protection grease. |
| Cable Entry | Cable entry protected by M20 cable gland. To be used with H05RN-F/ H07RN-F cable with 7-13mm. diameter. |
| Led | High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material. |
| Driver | High quality constant current LED driver. Conform to safety standard and electromagnetic compatibility standard. |
| Internal Wire | Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C. |
| Terminal Block | Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved. |
| | Class1 luminaire provided with the earth connection. |
| Caution | Installation work has to be carried on according to the enclosed installation manual. |
| Color | Black 01<br>Graphite 02<br>Dark Grey 03<br>Aluminum Silver 04<br>White 06<br>Corten 08 |

## Light Distribution







Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

*Due to the constancy of product development,
we reserve the right to alter all specification
without prior notice.

# ALPHA

## MINI ALPHA SQUARE ARM

SPOTLIGHT

LAST UPDATE: 13-02-2026

### Bug Report




Lum. Classification System (LCS)

| LCS | Zone | %Lumens | %Lamp | %Lum |
|---|---|---|---|---|
| FL | [0-30] | 398.0 | 38.3 | 45.2 |
| FM | [30-60] | 37.0 | 3.6 | 4.2 |
| FH | [60-80] | 4.0 | 0.4 | 0.5 |
| FVH | [80-90] | 0.1 | 0.0 | 0.0 |
| BL | [0-30] | 398.0 | 38.3 | 45.2 |
| BM | [30-60] | 37.0 | 3.6 | 4.2 |
| BH | [60-80] | 4.0 | 0.4 | 0.5 |
| BVH | [80-90] | 0.1 | 0.0 | 0.0 |
| UL | [90-100] | 0.0 | 0.0 | 0.0 |
| UH | [100-180] | 1.6 | 0.2 | 0.2 |
| Total | | 879.8 | 84.8 | 100.0 |
| BUG Rating | | B1-U1-G0 | | |

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

# ALPHA

## MINI ALPHA SQUARE ARM

SPOTLIGHT

LAST UPDATE: 13-02-2026

### Accessories



Ordering Code:
AUN-GSH-0007-00
Honeycomb louver, LED,
pre-assembly from factory



Ordering Code:
AUN-SOF-0021-00
Softening filter, LED,
pre-assembly from factory

Ordering Code:
AUN-CAB-0002-00
Cable HO7RN-F 3x1sqmm,
L= 2000, with UniBlock
anti-humidity kit,
pre-assembly from factory

Ordering Code:
AUN-CAB-0004-00
Cable HO7RN-F 3x1sqmm,
L= 500, with UniBlock
anti-humidity kit,
pre-assembly from factory

Ordering Code:
AUN-GHS-0029-XX
Glare shield cap

*Due to the constancy of product development,
we reserve the right to alter all specification
without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th