KORNER

KORNER2

POLE MOUNTED LIGHT

LAST UPDATE: 21-08-2026

KORNER is minimalistic linear shaped pole luminaire and wall light. The use of clear lines, closed surfaces and hidden mounting hardware provide an attractive unobtrusive appearance, and easy installation. The unique 16 stage paint process and use of virtually copper free aluminum alloys guarantee an ultra-long product lifetime. KORNER is suitable for medium mounting heights when using aluminum poles and high mounting heights of up to 8m in combination of steel poles. Existing circular poles can be utilized with the use of the innovative clamping system. KORNER uses high efficacy LED modules and CAD optimized optics. Ready for light management systems using the D4i protocol and Zhaga book 18 interface. Withstanding ambient temperatures of 50°C and electrical surges make KORNER applicable for most challenging environments.



Technical Data

Ordering Code :	7781-U-A-666-XX
Lamp :	LED
Beam :	T1 – Symmetric Long Side Throw
CCT :	3000 K
CRI :	CRI >80
SDCM :	SDCM = 3
Lamp Lumen :	8440 lm
Luminaire Lumen :	5130 lm
Lamp Wattage :	45 W
Luminaire Wattage :	50 W
Efficacy :	102 lm/W
Ambient Temperature :	25°C
Lumen Maintenance	L70B10 >60,000 h
Controller :	CASAMBI
Input Voltage :	220-240Vac 50/60Hz
Net Weight :	- kg.

Ordering code guide



A Product Code
B Reflector
C Electrical Component
D Lamp
E Color

Icon definition

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

KORNER

KORNER2

POLE MOUNTED LIGHT

LAST UPDATE: 21-08-2026

Specification

IEC Standard	IEC 60598-1 General Requirement
	IEC 60598-2-1 Fixed Luminaires
Protection	IP66 Class I
IK Rating	Protection against mechanical impact IK10 on body and IK08 on optical part.
Luminaires Body Housing	Extruded aluminum S6063 alloy body with low copper content.
	High-pressure die cast aluminum alloy body and components.
Coating Process	Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.
Diffuser	Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.
Lens	Molded PC lens from renowned manufacturers in various light distribution patterns.
Gasket	Weather resistant silicone gasket. Working temperature -40°C to +200°C.
External Screws	External screws are in stainless steel with protection grease.
Cable Entry	Cable entry protected by M20 cable gland. To be used with H05RN-F/ H07RN-F cable with 7-13mm. diameter.
Led	High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.
Driver	High quality constant current DALI driver with CASAMBI interface. Conform to applicable safety standards and electromagnetic compatibility.
Enhanced Protection	The luminaire is equipped with a 10kV surge protection device, the function of the protector is indicated by a LED, performance in compliance with IEC61643-11.
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.
Terminal Block	Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.
	Class1 luminaire provided with the earth connection.
Pre-Wire Cable	Pre-wired with 3x1.0 sqmm. H07RN-F neoprene cable. IMQ approved.
Caution	Installation work has to be carried on according to the enclosed installation manual.
Color	Black 01 Graphite 02 Dark Grey 03 Aluminum Silver 04 White 06

Light Distribution





Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

*Due to the constancy of product development,
we reserve the right to alter all specification
without prior notice.

KORNER

KORNER2

POLE MOUNTED LIGHT

LAST UPDATE: 21-08-2026

Bug Report



Lum. Classification System (LCS)

LCS	Zone	%Lumens	%Lamp	%Lum
FL	[0-30]	708.1	8.4	13.8
FM	[30-60]	1881.4	22.3	36.7
FH	[60-80]	643.4	7.6	12.5
FVH	[80-90]	4.0	0.0	0.1
BL	[0-30]	457.9	5.4	8.9
BM	[30-60]	1058.2	12.5	20.6
BH	[60-80]	368.9	4.4	7.2
BVH	[80-90]	3.1	0.0	0.1
UL	[90-100]	0.2	0.0	0.0
UH	[100-180]	3.0	0.0	0.1
Total		5128.2	60.6	100.0
BUG Rating		B2-U1-G1		

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

KORNER

KORNER2

POLE MOUNTED LIGHT

LAST UPDATE: 21-08-2026

Unilamp

Accessories

Ordering Code:
AUN-CON-0009-00
IP68 connection device, cable diameter 5-9.5mm, On-Off

Ordering Code:
AUN-CON-0010-00
IP68 connection device 3 pole, cable diameter 5-9.5mm, with distribution block

Ordering Code:
AUN-CON-0013-00
IP68 connection device, cable diameter 7-11.5mm, On-Off

Ordering Code:
AUN-ACB-0008-00
Anchor bolt kit, pole diameter 102mm and 151x102mm, galvanized steel pole

Ordering Code:
AUN-ACB-0022-00
Anchor bolt kit, aluminum pole



Ordering Code:
AUN-ACB-0023-00
Planted root, aluminum pole



Ordering Code:
AUN-ACB-0024-00
Planted root, galvanized steel pole

Ordering Code:
AUN-CLP-0010-XX
Pole clamp, pole diameter 60mm, single side luminaire mounting

Ordering Code:
AUN-CLP-0011-XX
Pole clamp, pole diameter 60mm, double sided luminaire mounting

Ordering Code:
AUN-CLP-0012-XX
Pole clamp, pole diameter 76mm, single side luminaire mounting

Ordering Code:
AUN-CLP-0013-XX
Pole clamp, pole diameter 76mm, double sided luminaire mounting

Ordering Code:
AUN-BRK-0004-XX
Mounting bracket

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

KORNER

KORNER2

POLE MOUNTED LIGHT

LAST UPDATE: 21-08-2026



Ordering Code:
ALUMINUM-POLE-FOR-KORNER
Please contact Sales Representative



Ordering Code:
STEEL-POLE-FOR-KORNER
Please contact Sales Representative



Ordering Code:
AUN-GSH-0071-XX
Glare shield cap

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th