

# SIRIUS

## SIRIUS 300 – CV

### LINEAR LIGHT | WALL SURFACE LIGHT



LAST UPDATE: 14-11-2025



SIRIUS a brand new linear light family features various mounting application types including in-ground walk over, wall mounted, ceiling mounted, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.



## Technical Data



|                       |                   |
|-----------------------|-------------------|
| Ordering Code :       | 8033-H-2-553-XX   |
| Lamp :                | LED               |
| Beam :                | 46°/16°           |
| CCT :                 | 4000 K            |
| CRI :                 | CRI >80           |
| SDCM :                | SDCM = 3          |
| Lamp Lumen :          | 1020 lm           |
| Luminaire Lumen :     | 720 lm            |
| Lamp Wattage :        | 7.3 W(24Vdc)      |
| Luminaire Wattage :   | 7.3 W             |
| Efficacy :            | 98 lm/W           |
| Ambient Temperature : | 50°C              |
| Lumen Maintenance     | L80B10 >108,000 h |
| Controller :          | Remote            |
| Input Voltage :       | 24Vdc             |
| Net Weight :          | 1.70 kg.          |

### Ordering code guide

XXXX-X-X-XXX-XX  
A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition



\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1  
Fax : +66(0)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

#### Specification

|                         |                                                                                                                                                                                                                                   |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IEC Standard            | IEC 60598-1 General Requirement<br>IEC 60598-2-1 Fixed Luminaires                                                                                                                                                                 |
| Protection              | IP67 Class III                                                                                                                                                                                                                    |
| IK Rating               | Protection against mechanical impact IK10 on body and IK08 on optical part.                                                                                                                                                       |
| Luminaires Body Housing | Extruded aluminum 56063 alloy body with low copper content.                                                                                                                                                                       |
| Coating Process         | Nano ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C. |
| Diffuser                | Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no accumulation of dust and water.                                                                 |
| Lens                    | Molded PC lens from renowned manufacturers in various light distribution patterns.                                                                                                                                                |
| Adjustable Optic        | Wall mount with adjustable arms.                                                                                                                                                                                                  |
| Gasket                  | Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.                                                                                                                       |
| External Screws         | External screws are in stainless steel with protection grease.                                                                                                                                                                    |
| Cable Entry             | Cable entry protected by M20 cable gland. To be used with H05RN-F/ H07RN-F cable with 7-13mm. diameter.                                                                                                                           |
| Led                     | High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.                                                                                        |
| Driver                  | Driver is not included and has to be ordered separately.                                                                                                                                                                          |
| Internal Wire           | Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.                                                                                                                 |
| Terminal Block          | Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.                                                                                                                                            |
| Pre-Wire Cable          | Pre-wired with 2x1.0 sqmm. H07RN-F neoprene cable. IMQ approved.<br>Equipped with anti-humidity kit.                                                                                                                              |
| Caution                 | Installation work has to be carried on according to the enclosed installation manual.                                                                                                                                             |
| Color                   | <div> <div>Black O1</div> <div>Graphite O2</div> <div>Dark Grey O3</div> <div>Aluminum Silver O4</div> <div>White O6</div> <div>Corten O8</div> </div>                                                                            |

#### Light Distribution



#### Accessories




Ordering Code:  
AUN-CON-0009-00  
IP68 connection device,  
cable diameter 5-9.5mm,  
On-Off




Ordering Code:  
AUN-CON-0010-00  
IP68 connection device 3  
pole, cable diameter  
5-9.5mm, with distribution  
block



Ordering Code:  
AUN-BRK-0001-XX  
Mounting bracket, L=  
250mm, adjustable




Ordering Code:  
AUN-DRG-0011-00  
LED constant voltage  
driver, 24VDC, 150W




Ordering Code:  
AUN-SOF-0033-00  
Softening filter, LED,  
pre-assembly from factory




Ordering Code:  
AUN-GHS-0023-00  
Glare shield louver,  
Bi-Symmetric beam



Ordering Code:  
AUN-DRG-0027-00  
LED constant voltage  
driver, 24VDC, 72W



Ordering Code:  
AUN-DRG-0100-00  
LED constant voltage  
driver, 24VDC, 60W, DALI



Ordering Code:  
AUN-DRG-0101-00  
LED constant voltage  
driver, 24VDC, 120W, DALI



Ordering Code:  
AUN-DRG-0126-00  
LED constant current  
driver, 250mA, 12W, with  
IP67 GFR polymer  
enclosure, On-Off, BLACK